

Quick edge trim guide

A170

Fascia Trim

Dimensions
Girth: 170mm
Depth: 65mm

Application
Fitted to roof edges to allow drainage.

A200

Fascia Trim

Dimensions
Girth: 200mm
Depth: 90mm

Application
Fitted to roof edge to allow drainage into gutter. Compatible with C1, C2 and C4 corner trims.

A250

Fascia Trim

Dimensions
Girth: 250mm
Depth: 140mm

Application
Roof edge detail to cover insulation. Usually used with a warm roof specification. Deep fascia to allow gutter penetration.

B230

Raised Edge Trim

Dimensions
Girth: 230mm
Depth: 105mm

Application
Flat roof edge detail to prevent water run off. Drip matches A170.

B260

Raised Edge Trim

Dimensions
Girth: 260mm
Depth: 125mm

Application
Flat roof edge detail to prevent water run off. Compatible with C1, C2 and C4 corner trims.

B300

Raised Edge Trim

Dimensions
Girth: 300mm
Depth: 180mm

Application
Deep fascia raised edge trim. Usually used with a warm roof configuration. Drip matches with A250 trim.

C100

Simulated Lead Flashing

Dimensions
Vertical cover: 100mm
Wall penetration: 35mm

Application
Replaces traditional lead flashing. Dark grey, non-adhesive finish to simulate the appearance of lead. Do not topcoat.

C100MT

Simulated Lead Flashing with Moisture Trap

Dimensions
Vertical cover: 100mm
Wall penetration: 35mm

Application
As C100 with integral self-securing moisture trap.

C100L

Simulated Lead Flashing Long Leg

Dimensions
Vertical cover: 100mm
Wall penetration: 50mm

Application
As C100 with deep wall penetration.

C100LMT

Simulated Lead Flashing Long with Moisture Trap

Dimensions
Vertical cover: 100mm
Wall penetration: 50mm

Application
As C100 with deep wall penetration and integral self-securing moisture trap.

C150

Simulated Lead Flashing

Dimensions
Vertical cover: 150mm
Wall penetration: 35mm

Application
Replaces traditional lead flashing. Dark grey, non-adhesive finish to simulate the appearance of lead. Do not topcoat.

C150MT

Simulated Lead Flashing with Moisture Trap

Dimensions
Vertical cover: 150mm
Wall penetration: 35mm

Application
As C150 with integral self-securing moisture trap.

C150L

Simulated Lead Flashing Long Leg

Dimensions
Vertical cover: 150mm
Wall penetration: 50mm

Application
As C150 with deep wall penetration.

D260

Wall Fillet

Dimensions
Girth: 260mm
Fillet: 135 & 70mm
Upstand height: 120mm

Application
Asymmetric fillet trim for use against abutting walls. Also provides expansion and perimeter ventilation.

D300

Long Flange Wall Fillet

Dimensions
Girth: 260mm
Fillet: 175 & 70mm
Upstand height: 120mm

Application
Extra wide asymmetric fillet for use against abutting walls. Also provides expansion and perimeter ventilation.

E35/40

Simulated Lead Rolled Joint (Rolled Rib)

Dimensions
Girth: 130mm
Flanges: 20mm
Height: 40mm
Roll width: 35mm

Application
Used to simulate the appearance of raised rolled lead joints. Also provides expansion. Compatible with C6 preformed closures.

E280

Raised Ridge Roll

Dimensions
Girth: 280mm
Flanges: 90mm
Height: 50mm

Application
Used as an expansion joint on larger roofs and to create rolls on any ridge details. Compatible with C5 preformed closures.

F300/600/900 Flat Flashing

Dimensions
Max width: 900mm
Min width: 300mm
Max length: 20m

Application
Flat section for use as continuous flashing under slates at a roof junction. It can also be used as a gutter lining.

G180

Gully Trim/Expansion Joint

Dimensions
Girth: 180mm
Flanges: 30mm
Depth: 15mm
Trough width: 80mm

Application
Used on larger roofs to aid drainage and to ensure gapping of underlying timber to facilitate expansion.

S500

Soffit Trim

Dimensions
Girth: 450mm
Depth: 225mm

Application
To fully encapsulate a concrete edge or similar roof edge detail.

AT195Int

Internal Angle Trim

Dimensions
Girth: 195mm
Flange widths: 105 & 85mm

Application
High adhesion surface on inner face for forming upstands, gutter floors etc.

AT195Ext

External Angle Trim

Dimensions
Girth: 195mm
Flange widths: 85 & 105mm

Application
High adhesion finish on outer face for step details, cover flashings etc.

C1

Universal External Corner

Description
Hot press moulded GRP pre-formed external corner.

Application
For use with A200 and B260 profiles to form a left of right hand corner.

C2

Fillet to Trim

Description
Right and left hand mouldings available

Application
For use where a flat roof meets an abutting wall. Compatible with A200, B260 and D260 profiles.

C3 (Int)

Internal Fillet Corner

Description
Internal corner fillet trim.

Application
Used as a pre-formed internal corner for D260 fillet trim. Avoids mitring in situ.

C3 (Ext)

External Fillet Corner

Dimensions
External corner fillet trim

Application
Used as a pre-formed corner for the D260 fillet profile. Avoids mitring in situ.

C4

Universal Internal Corner

Description
Hot press moulded GRP pre-formed internal corner.

Application
For use with A200 and B260 profiles to form a left or right hand corner.

C5

Roof Ridge Closure

Description
Preformed roof ridge closure.

Application
Pre-formed closure for use with E280 profiles.

C6

ER35/40 Rolled Rib Closure

Description
Preformed roof ridge closure.

Application
Pre-formed closure trim for use with ER35/40 profiles.